


4"SR - HYDRAULIQUES SEULES

A TURBINES FLOTTANTES



TYPE	DIMENSIONS en mm						Poids pompe complète kg			Code
	DN	h1	h2 Mono	h2 Tri	h Mono	hTri	kW	Mono	Tri	
4SR1/13	1"1/4	400	242	223	642	623	0.55	14	13	J1A1010
4SR1/18	1"1/4	517	271	242	788	759	0.55	16	15	J1A1020
4SR1/25	1"1/4	646	298	271	944	917	0.75	19	18	J1A1030
4SR1/35	1"1/4	856	327	298	1183	1154	1.10	22	21	J1A1040
4SR1/45	1"1/4	1065	356	327	1421	1392	1.50	26	24	J1A1050
4SR2/7	1"1/4	290	242	223	532	513	0.55	12	11	J1A107X
4SR2/10	1"1/4	345	271	242	616	587	0.55	14	12	J1A108X
4SR2/13	1"1/4	400	298	271	698	671	0.75	16	14	J1A109X
4SR2/20	1"1/4	554	327	298	881	852	1.10	18	17	J1A110X
4SR2/27	1"1/4	683	356	327	1039	1010	1.50	22	21	J1A111X
4SR2/39	1"1/4	929	460	356	1389	1285	2.20	29	25	J1A111Y
4SR4/7	1"1/4	314	271	242	585	556	0.55	14	12	J1A1120
4SR4/9	1"1/4	358	298	271	656	629	0.75	15	14	J1A113X
4SR4/14	1"1/4	468	327	298	795	766	1.10	18	16	J1A114X
4SR4/18	1"1/4	580	356	327	936	907	1.50	21	18	J1A115X
4SR4/26	1"1/4	756	460	356	1216	1112	2.20	26	21	J1A1160
4SR4/35	1"1/4	978	-	423	-	1401	3.00 (*)	-	27	J1A1170
4SR4/46	1"1/4	1295	-	583	-	1878	4.00	-	40	J1A1175
4SR4/60	1"1/4	1652	-	698	-	2350	5.50	-	50	J1A1177
4SR6/4	2"	281	271	242	552	523	0.55	14	13	J1A1180
4SR6/6	2"	341	298	271	639	612	0.75	15	13	J1A1190
4SR6/9	2"	431	327	298	758	729	1.10	17	15	J1A1200
4SR6/13	2"	576	356	327	932	903	1.50	20	19	J1A1210
4SR6/17	2"	695	460	356	1155	1051	2.20	26	21	J1A1220
4SR6/23	2"	900	-	423	-	1323	3.00 (*)	-	25	J1A1230
4SR6/31	2"	1164	-	583	-	1747	4.00	-	37	J1A1240
4SR6/42	2"	1519	-	698	-	2217	5.50	-	45	J1A1250
4SR6/56	2"	2063	-	774	-	2837	7.50	-	56	J1A1255
4SR8/4	2"	281	298	271	579	552	0.75	15	13	J1A1260
4SR8/7	2"	371	327	298	698	669	1.10	17	15	J1A1270
4SR8/9	2"	431	356	327	787	758	1.50	17	16	J1A1280
4SR8/13	2"	576	460	356	1036	932	2.20	25	19	J1A1290
4SR8/17	2"	695	-	423	-	1118	3.00	-	23	J1A1300
4SR8/23	2"	900	-	583	-	1483	4.00	-	34	J1A1310
4SR8/31	2"	1164	-	698	-	1862	5.50	-	42	J1A1320
4SR8/42	2"	1519	-	774	-	2293	7.50	-	49	J1A1330
4SR10/5	2"	416	327	298	743	714	1.10	17	16	J1A1340
4SR10/7	2"	518	356	327	874	845	1.50	20	18	J1A1350
4SR10/10	2"	709	460	356	1169	1065	2.20	26	21	J1A1360
4SR10/15	2"	1001	-	423	-	1424	3.00	-	27	J1A1370
4SR10/20	2"	1256	-	583	-	1839	4.00	-	37	J1A1380
4SR10/26	2"	1599	-	698	-	2297	5.50	-	45	J1A1390
4SR10/35	2"	2095	-	774	-	2869	7.50	-	54	J1A1400
4SR12/4	2"	365	327	298	692	663	1.10	17	16	J1A1410
4SR12/6	2"	467	356	327	823	794	1.50	19	18	J1A1420
4SR12/9	2"	658	460	356	1118	1014	2.20	26	21	J1A1430
4SR12/12	2"	810	-	423	-	1233	3.00	-	27	J1A1440
4SR12/16	2"	1052	-	583	-	1635	4.00	-	35	J1A1450
4SR12/22	2"	1358	-	698	-	2056	5.50	-	43	J1A1460
4SR12/29	2"	1752	-	774	-	2526	7.50	-	49	J1A1470
4SR15/5	2"	421	356	327	777	748	1.50	19	18	J1A1480
4SR15/7	2"	525	460	356	985	881	2.20	24	20	J1A1490
4SR15/10	2"	719	-	423	-	1142	3.00	-	24	J1A1500
4SR15/13	2"	874	-	583	-	1457	4.00	-	33	J1A1510
4SR15/18	2"	1172	-	698	-	1870	5.50	-	41	J1A1520
4SR15/24	2"	1521	-	774	-	2295	7.50	-	48	J1A1530



(*) : Moteur butée renforcée 3 kW 6500 N.